

LOWER AND UPPER BOUNDS ON THE RANDOMNESS COMPLEXITY OF PRIVATE COMPUTATIONS OF AND*

EYAL KUSHILEVITZ[†], RAFAIL OSTROVSKY[‡], EMMANUEL PROUFF[§], ADI ROSÉN[¶],
ADRIAN THILLARD^{||}, AND DAMIEN VERGNAUD[#]

Abstract. We consider multi-party information-theoretic private protocols, and specifically their randomness complexity. The randomness complexity of private protocols is of interest both because random bits are considered a scarce resource, and because of the relation between that complexity measure and other complexity measures of boolean functions such as the circuit size or the sensitivity of the function being computed [19, 13].

More concretely, we consider the randomness complexity of the basic boolean function **and**, that serves as a building block in the design of many private protocols. We show that **and** cannot be privately computed using a single random bit, thus giving the first non-trivial lower bound on the 1-private randomness complexity of an explicit boolean function, $f : \{0, 1\}^n \rightarrow \{0, 1\}$. We further show that **and**, on any number of inputs n (one input bit per player), can be privately computed using 8 random bits (and 7 random bits in the special case of $n = 3$ players), improving the upper bound of 73 random bits implicit in [19]. Together with our lower bound, we thus approach the exact determination of the randomness complexity of **and**. To the best of our knowledge, the exact randomness complexity of private computation is not known for any explicit function (except for **xor**, which is 1-random, and for several degenerate functions).

1. Introduction. A multi-party *private* protocol for computing a function f is a distributed protocol that allows $n \geq 3$ players P_i , for $0 \leq i \leq n - 1$, each possessing an individual secret input x_i , to compute the value of $f(x)$ in a way that does not reveal any “unnecessary” information to any player (we remark that the two-party case, $n = 2$, is known to be qualitatively different [8]). The protocol proceeds in rounds, where in each round each player sends a message to each other player, over a secure point-to-point channel. The privacy property of such a protocol means that no player can learn “anything” (in an information-theoretic sense) from the execution of the protocol, except what is implied by the value of $f(x)$ and its own input. In particular, the players do not learn anything about the inputs of the other players. Private computation in this setting was the subject of considerable research, see e.g., [3, 7, 1, 8, 17, 19, 13]. In addition to its theoretical interest, this setting (and its

*A preliminary version of this paper appeared in the proceedings of TCC 2019 [18].

[†]Department of Computer Science, Technion, Israel. Email: eyalk@cs.technion.ac.il. Research supported by ISF grant 1709/14, BSF grant 2018393, NSF-BSF grant 2015782, and a grant from the Ministry of Science and Technology, Israel, and the Dept. of Science and Technology, Government of India.

[‡]UCLA Department of Computer Science and Department of Mathematics. Email: rafael@cs.ucla.edu. This author is supported in part by DARPA under Cooperative Agreement No: HR0011-20-2-0025, NSF-BSF Grant1619348, US-Israel BSF grant 2012366, Google Faculty Award, JP Morgan Faculty Award, IBM Faculty Research Award, Xerox Faculty Research Award, OKAWA Foundation Research Award, B. John Garrick Foundation Award, Teradata Research Award, and Lockheed-Martin Corporation Research Award. The views and conclusions contained herein are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of DARPA, the Department of Defense, or the U.S. Government. The U.S. Government is authorized to reproduce and distribute reprints for governmental purposes not withstanding any copyright annotation therein.

[§]ANSSI, Paris, France, Sorbonne Université, CNRS, Laboratoire dinformatique de Paris 6, LIP6, F-75005 Paris, France. Email: emmanuel.prouff@ssi.gouv.fr.

[¶]CNRS and Université de Paris, France. Email: adiro@irif.fr.

^{||}ANSSI, Paris, France. Email: adrian.thillard@ssi.gouv.fr.

[#]Sorbonne Université, CNRS, Laboratoire dinformatique de Paris 6, LIP6, F-75005 Paris, France, Institut Universitaire de France. Email: damien.vergnaud@lip6.fr.

variants) constitutes the foundation of many cryptographic applications: On top of the generality of secure computation in this setting, due to the existence of (efficient) compilers that can transform a generic representation (e.g., a boolean circuit) of any function f into a secure protocol computing the same function f [3, 7], concrete applications include secure computation of useful functions such as voting, auctions (with first actual implementations and deployment [6]), or Private Set-Intersection (PSI), which by itself is a useful building-block for other cryptographic applications. The above mentioned applications (and generality) hold also for the computational version of secure computation. The advantages of the information-theoretic are in that there is no need for unproven computational assumptions, and in that its concrete efficiency is typically better, because it avoids using heavy cryptographic primitives (the main disadvantage of the information-theoretic version is that it is impossible to have in some important cases such as for most *two-party* secure computation tasks).

Randomness is necessary in order to perform private computations involving more than two players (except for the computation of very degenerate functions). That is, the players must have access to (private) random sources. As randomness is regarded as a scarce resource, methods for saving random bits in various contexts have been suggested in the literature, see, e.g., [22, 15] for surveys. Thus, an interesting research topic is the design of randomness-efficient private protocols, and the quantification of the amount of randomness needed to perform private computations of various functions and under various constraints. This line of research has received considerable attention, see, e.g., [21, 17, 19, 5, 4, 16, 12, 23].

As in most of the work on the randomness complexity of private computations, we concentrate here on the computation of boolean functions, where the input x_i of each player is a single bit. Previous work on the randomness complexity of private computations revealed that there is a tradeoff between randomness and time (i.e., number of communication rounds) for the private computation of **xor** [21], or gave lower bounds on the number of rounds necessary to privately compute any function, in terms of the sensitivity of the function and the amount of randomness used [13]. However, if one is allowed an arbitrary number of rounds for the computation then, prior to the present work, there were no known lower bounds on the number of random bits necessary for private protocols computing explicit boolean functions (except that some randomness is indeed necessary, i.e., no deterministic private protocol exists).¹ In fact, Kushilevitz et al. [19] gave a relation between the number of random bits necessary to privately compute a function $f : \{0, 1\}^n \rightarrow \{0, 1\}$, and the Boolean circuit size necessary to compute f ; it is proved, among other things, that the class of boolean functions that have $O(1)$ -random, private,² protocols is equal to the class of boolean functions that have linear size circuits. This, perhaps surprising, connection to circuit size explains the difficulty of proving $\omega(1)$ lower bounds on the number of random bits necessary for the private computation of any explicit boolean function f , as such a result would imply superlinear lower bounds on the circuit size of f – a notoriously difficult problem.³ Additional connections between the randomness complexity of

¹Recently, a lower bound on the number of random bits necessary for the private computation of the Disjointness function was obtained [23]. However, for the Disjointness function each player has $m \geq 1$ bits of input. Furthermore, the obtained lower bound is of $\Omega(m)$, and the hidden constant is less than 1. Thus, for the special case of **and** (Disjointness with $m = 1$), the lower bound of [23] only implies, in our context, the trivial claim that **and** cannot be privately computed by a deterministic protocol.

²In this paper we consider only the case of 1-private protocols which we call for simplicity “private”. See Definition 2.4 for a formal definition.

³When the protocol has to be resilient against coalitions of $t > 1$ players (so called t -private

privately computing a function f to other complexity measures of f , such as its sensitivity, have been shown in, e.g., [21, 5, 20].

This leaves the interesting, and perhaps feasible, task to determine the exact randomness complexity of the private computation of boolean functions of linear circuit size, where each player has a single input bit. This class of functions includes quite a few interesting functions f and, in particular, the basic functions **xor** and **and**. Indeed, the functions **xor** and **and** serve as basic building blocks for private protocols that rely on the boolean-circuit representation of f (more generally, *addition* and *multiplication* are used as building blocks for protocols that use the *arithmetic*-circuit representation of f). In the context of lower bounds for *communication* complexity of private protocols, these building blocks also serve as the center of analysis (as a first step for a more general understanding), see, e.g., [9, 10, 11].

It is known that **xor** can be computed privately using a single random bit, for any number of players, and this is optimal since no deterministic private multiparty protocol can exist (see [21]). To the best of our knowledge, there is no exact determination of the randomness complexity of private computation for any other explicit function. Furthermore, prior to the present paper, there was no lower bound showing for any explicit boolean function that it cannot be privately computed (in the natural setting that we consider here, i.e., where each player has one input bit) using a single random bit.

In this paper, we give the first such lower bound, showing that the function **and** cannot be privately computed using a single random bit.⁴ We further make the first step towards determining the exact randomness complexity of the private computation of **and** by showing an improved upper bound of 8 on the number of random bits necessary for such computation, and we strengthen this upper bound to 7 for the special case of 3 players. We note that the function **and** is very different than the function **xor**, in the context of privacy, as there is an output value (i.e., 1) that completely reveals the inputs.

The rest of the paper is organized as follows. In Section 2, we define the model and the complexity measures that we consider. In Section 4, we prove that the private computation of **and** cannot be performed with a single random bit. In Section 5, we give a number of upper bounds on the randomness complexity of private computation of **and**.

2. Preliminaries. Let $f : \{0, 1\}^n \rightarrow \{0, 1\}$ be any Boolean function. A set of n players P_i ($0 \leq i \leq n - 1$), each possessing a single input bit x_i (known *only* to P_i), collaborate in a protocol to compute the value of $f(x)$. The protocol operates in rounds. In each round each player may toss some (fair) random coins, and then sends messages to the other players (messages are sent over private channels so that other than the intended receiver no other player can see them). After sending its messages, each player receives the messages sent to it by the other players in the current round. Without loss of generality (because we are not interested in this paper in the number

protocols) several $\omega(1)$ lower bounds on the number of random bits necessary for private protocols for explicit functions have been proved. Kushilevitz and Mansour [17] proved that any t -private protocol for **xor** requires at least t random bits. Blundo et al. [5] gave lower bounds for two special cases. Namely, they proved that if $t = n - c$, for some constant c , then $\Omega(n^2)$ random bits are necessary for the private computation of **xor**, and if $t \geq (2 - \sqrt{2})n$, then $\Omega(n)$ random bits are necessary. Gal and Rosén [14] proved that $\Omega(\log n)$ random bits are necessary for 2-private computation of **xor**.

⁴In a different setting, namely, where there are two input players, Alice and Bob, and a third output player, Charlie, Data et al. [12] also study the randomness (and communication) complexity of secure computation (in particular of the **and** function; see [12, Thm. 11]).

of rounds), we assume that the messages sent by the players consist of single bits. In addition, each player locally outputs the value of the function at a certain round. We say that the protocol computes the function $f : \{0, 1\}^n \rightarrow \{0, 1\}$ if, for every input $x \in \{0, 1\}^n$, and for any outcome of all coin tosses, the output produced by each player is always $f(x)$ (i.e., perfect correctness).

To formally define a protocol, we first define the notion of a *view* of a player.

DEFINITION 2.1. (View) *The view of player P_i at round $t \geq 1$, denoted V_i^t , consists of the input bit to player P_i , i.e. x_i , the messages received by P_i in rounds 1 to $t-1$, and the results of the coin tosses performed by player P_i in rounds 1 to t . Let $\mathcal{V}_i^t$ be the set of possible views of player P_i at round t . Let $\hat{V}_i^t$ be the view V_i^t without the coins tossed at round t , and let $\hat{\mathcal{V}}_i^t$ be the set of possible values of $\hat{V}_i^t$.*

DEFINITION 2.2. (Protocol) *A protocol consists of a sequence of rounds, where each round $t \geq 1$ is formally defined by the following functions:*

- $S_i^{t,\ell} : (\hat{\mathcal{V}}_i^t \times \{0, 1\}^{\ell-1}) \rightarrow \{\text{stop}, \text{toss}\}$, for $\ell \geq 1$, defining if another random coin is to be tossed by player P_i , given $\hat{V}_i^t$ and the values of the $\ell-1$ random coins tossed so far by player P_i in round t .
- $m_{i,j}^t : \mathcal{V}_i^t \rightarrow \{0, 1\}$, for $0 \leq i, j \leq n-1$, defining the message P_i sends to P_j at round t .
- $O_i^t : \mathcal{V}_i^t \rightarrow \{0, 1, \perp\}$, for $0 \leq i \leq n-1$, defining if and what value player P_i outputs at round t . Since the views are increasing, we can require that each player output a non-null output only in one round.

Sometimes it is more convenient to model the coin tossing done by each player, as a set of binary random tapes R_i , each R_i being provided to player P_i . The number of random coins tossed by player P_i is the number of random bits it reads from its random tape.

We denote by r_i a specific random tape provided to player P_i , by $\vec{r} = (r_1, \dots, r_n)$ the vector of random tapes of all the players, and by $\vec{R} = (R_1, \dots, R_n)$ the random variable for these tapes. Note that if we fix $\vec{r}$, we obtain a deterministic protocol.

DEFINITION 2.3. (Randomness Complexity) *A d -random protocol is a protocol such that, for any input assignment x , the total number of coins tossed by all players in any execution is at most d . The randomness complexity of a function f is the smallest such d , over all private protocols (as defined next) that compute f .*

Our main question in this paper is what is the randomness complexity of privately computing the function **and**.

Informally, *privacy* with respect to player P_i means that player P_i cannot learn anything (in particular, the inputs of other players) from the messages it receives, except what is implied by its input bit, and the output value of the function f being computed.⁵ Formally, denote by c_i a specific sequence of messages received by P_i , and by C_i the random variable (depending also on $\vec{R}$) for the sequence of messages received by P_i . We define:

DEFINITION 2.4. (Privacy) *A protocol $\mathcal{A}$ for computing a function f is private with respect to player P_i if, for any two input vectors x and y such that $f(x) = f(y)$ and $x_i = y_i$, for any sequence of messages c_i , and for any random tape r_i provided to*

⁵In the literature, a more general notion of privacy, called t -privacy, is often considered, where any set of at most t players cannot learn anything from the messages received by all of them. In this paper, we consider only 1-privacy, and call it “privacy” for simplicity.

P_i ,

$$\Pr[C_i = c_i | r_i, x] = \Pr[C_i = c_i | r_i, y],$$

where the probability is over the random tapes of all other players.

A protocol is said to be private if it is private with respect to all n players.

We note that in the information-theoretic setting that we consider in this paper, where parties are semi-honest (and there are no additional issues such as adaptivity and composability), the standard definitions of privacy that we formulate in the definition above are equivalent to real-ideal definitions of security that use (computationally unbounded) simulators, cf. [15]

3. Technical Overview. In this section we give a technical overview of our results, both the lower bound and the upper bounds. This overview is intended to explain the high level structures of our proofs and protocols, without getting into various technical details. In order to keep the main parts of the paper self contained and easy to read, some of the explanation given here are also repeated in the sequel.

3.1. Overview of the Lower Bound. Our lower bound asserts that the private computation of the function **and**, for $n \geq 3$ players, cannot be performed using a single random bit (Theorem 4.7). We first note that a lower bound on the number of random bits of private computation for $n > 3$ does not follow from a lower bound for $n = 3$ because, in general, simulating a protocol for $n > 3$ players using 3 players may violate the privacy requirement. Thus our proof proves the claim directly for any $n \geq 3$.

Our line of proof is as follows. We first claim that any protocol can be transformed into a protocol in *canonical form*, without increasing the number of random bits used. A protocol in canonical form is a protocol without any “unnecessary messages”, where, roughly speaking, an “unnecessary message” is a message whose receiver can compute by itself (Definition 4.1). We then prove that for any private 1-random protocol for **and**, there must be one player (w.l.o.g player P_0), which is the player that tosses the single random bit in all executions of the protocol (Lemma 4.2). This allows us to represent all messages in the protocol as polynomials in the n input bits and the single random bit, and prove, for any 1-random private protocol in canonical form for **and**, that each player can receive at most a single message, which has to be of a specific form, concretely a linear function of the input bits and the random bit (Lemma 4.3). But, then we prove that such message does not allow any player to compute the value of the function **and** (Lemma 4.6). This completes the proof of the impossibility result.

3.2. Overview of the Upper Bounds. For the upper bounds, we first present a protocol using 8 random bits, applicable to any odd number of players $n \geq 3$. This protocol serves to introduce the main ideas of our protocols, and is also the basis for a somewhat improved protocol for $n = 3$, that uses 7 random bits. We then extend this protocol to be applicable to any $n \geq 4$ (even or odd), still using 8 random bits; this requires some additional technical effort.

The general structure of all our protocols is as follows. The protocols have three phases: an initialization phase, a computation phase, and a final phase. In the initialization phase random bits are tossed and distributed to the various players. The computation phase, the heart of our protocols, proceeds in $n-1$ rounds, where round i involves players P_i and P_{i-1} . These rounds are designed such that at the end of round $i \geq 1$, player P_i has the value $y_i = q_0 \oplus q_1 \oplus \Pi_{j=0}^i x_j$, which is the partial **and** of the first $i+1$ input bits, “masked” with q_0 and q_1 which are random bits tossed by player P_0 in the initialization phase. Since each player P_i , $i > 0$, receives from P_0 (in the initialization phase) exactly one of q_0 and q_1 (and the other value remains hidden from

it), the value y_i does not reveal any information to P_i . In the final phase the value y_{n-1} is “deciphered” so that the protocol computes $\Pi_{j=0}^{n-1} x_j = \text{and}(x_0, \dots, x_{n-1})$.

To implement round number i of the computation phase, players P_{i-1} and P_i engage in a 1-out-of-2 Oblivious Transfer protocol: the idea is that if the input of P_i is $x_i = 1$ then P_i fetches from P_{i-1} the value y_{i-1} ; observe that when $x_i = 1$, $y_i = y_{i-1}$. Otherwise, if $x_i = 0$, P_i fetches from P_{i-1} the random bit that P_{i-1} received from P_0 (which is one of the random bits q_0 and q_1), and then by itself constructs y_i (in this case y_i is merely $y_i = q_0 \oplus q_1$).

Securely performing the various OT protocols with 6 random bits overall is simpler when the number of players is odd. In this case we use alternately two separate sets of 3 random bits, one set tossed by P_0 and one tossed by P_{n-1} . When the number of players is even, this use of the random bits will not preserve privacy, because the random bits to be used for phase number $n - 1$ (involving players P_{n-1} and P_{n-2}) would be those tossed by P_{n-1} . We therefore need to slightly modify the final round of the computation phase, and further to distribute and reuse the random bits for the OT protocols in a more sophisticated way (see Section 5.2.2).

4. Lower Bound. In this section we prove that private computation of **and** of n bits, $n \geq 3$, cannot be performed with a single random bit. We note that a lower bound on the number of random bits of private computation for $n > 3$ does not follow from a lower bound for $n = 3$ because, in general, simulating a protocol for $n > 3$ players using 3 players may violate the privacy requirement.

Our result for **and** is in contrast to the situation for the function **xor**, which can be computed privately using a single random bit. Our result constitutes, to the best of our knowledge, the first lower bound that quantifies the amount of randomness needed to privately compute an explicit boolean function (without any limitation on the protocol, such as its round complexity).

In the course of this proof, we denote by $\vec{1}$ the all-1 input of length n , and by $\bar{e}_S$, for $S \subseteq \{1, \dots, n\}$, the input assignment of all 1’s *except* at the coordinates in S . Specifically, we use $\bar{e}_j$ to denote the vector with 0 at position j and 1’s elsewhere⁶ and $\bar{e}_{i,j}$ to denote the vector with 0’s at positions i, j and 1’s elsewhere.

We first give a number of definitions related to the messages in a protocol. A message $m_{i,j}^t$ is a *constant message* if its value is the same given any input vector x and any vector of random tapes $\vec{r}$. A message $m_{i,j}^t$ is a *useless message* if (1) $m_{i,j}^t$ is not a constant message, but (2) $m_{i,j}^t$ ’s value is still determined by the view of the receiving player P_j at round t , i.e. V_j^t , as well as the messages that P_j received in round t before receiving $m_{i,j}^t$ (we assume here that in a given round, a player receives the messages in increasing order of the index of the sending player); that is, there is a function $\hat{m}_{i,j}^t : \mathcal{V}_j^t \times \{0, 1\}^{i-1} \rightarrow \{0, 1\}$, such that for all executions of the protocol, $m_{i,j}^t(V_i^t) = \hat{m}_{i,j}^t(V_j^t, m_{1,j}^t, \dots, m_{i-1,j}^t)$. We observe that if a message $m_{i,j}^t$ is useless, then its value can be determined by P_j just before P_j receives it. Thus, one can w.l.o.g. eliminate from a given protocol all useless messages by replacing them by constant messages as the receiving player will just compute what should have been the value of the deleted message. We can thus assume w.l.o.g. that any protocol π is in *canonical form* which we define as follows:

DEFINITION 4.1. (Protocol in Canonical Form)

A protocol is in canonical form if

⁶Not to be confused with the j -th unit vector, where the only 1 is in position j , commonly denoted e_j .

1. *There is no round in the protocol in which all $n(n-1)$ messages are constant messages; and*
2. *There is no useless message in the protocol.*

Now, assume towards a contradiction that a protocol π is a 1-random private protocol (in canonical form) to compute **and**, for $n \geq 3$ players.

We start with the following lemma.

LEMMA 4.2. *Consider the protocol π . There is one player, w.l.o.g. denoted P_0 , such that for all inputs x and for all vectors of random tapes $\vec{r}$, player P_0 tosses exactly one random bit in π .*

Proof. For π to compute **and** there must be at least one non-constant message in π . Consider an arbitrary such message, m , sent in round $t = 1$ (since π is in canonical form there must be at least one such message in round $t = 1$) from w.l.o.g. player P_0 to, say, player P_j . Since the message m is sent in round $t = 1$, it can depend only on x_0 and the random bits tossed by P_0 by round $t = 1$. To preserve privacy with respect to P_j , the message m has to have the same distribution when $x_0 = 0$ and when $x_0 = 1$. Since π is 1-random, the number of random bits tossed by any single player, in particular P_0 , in any execution of the protocol, is at most 1. It follows that $\Pr[m = 0] = 1/2$, and $\Pr[m = 1] = 1/2$ regardless of the value of x_0 , thus P_0 must toss a random bit by round $t = 1$ whether $x_i = 0$ or $x_i = 1$. Since π is 1-random, P_0 does not toss any additional random bits in any execution. Thus, player P_0 (the sender of m) tosses in π exactly one random bit. $\square$

Since π is 1-random, it also follows from the above lemma that no other random bit is tossed in π in any execution (by any player). We can therefore denote by r the single random bit tossed in π . Thus, since all messages in π can depend only on the input bits, x_i , $0 \leq i \leq n-1$, and the single random bit r tossed by player P_0 , it follows that we may express any message sent in π as a sum of monomials in x_i , $0 \leq i \leq n-1$, and r . We now analyze some properties of the messages of the (assumed) protocol π .

LEMMA 4.3. *For each non-constant messages m sent in π there exists a set $S \subseteq \{0, \dots, n-1\}$ such that $m = r \oplus \sum_{i \in S} x_i$ or $m = 1 \oplus r \oplus \sum_{i \in S} x_i$. No player receives during the execution of π more than one non-constant message.*

Proof. We prove the lemma by induction on the round number $t \geq 1$, i.e., we prove that until round $t \geq 1$ all non-constant messages are of the form $m = r \oplus \sum_{i \in S} x_i$ or $m = 1 \oplus r \oplus \sum_{i \in S} x_i$, for some $S \subseteq \{0, \dots, n-1\}$, and that no player receives by the end of round t more than one non-constant message.

For the basis of the induction consider the first round $t = 1$ and the messages sent and received in this round. A non-constant message in the first round can be sent only by player P_0 as otherwise it consists of only the input bit of the sending player (or its negation) and the privacy property will be violated. Since no message is received before the messages of the first round are sent, the messages sent by player P_0 at round $t = 1$ are a function of only r and x_0 . We argue that such message, unless it is constant, has to be of the form $m = r \oplus x_0$ (or $m = 1 \oplus r \oplus x_0$) or of the form $m = r$ (or $m = 1 \oplus r$): since m depends only on r and x_0 , the monomials in m can only be 0, 1, x_0 , r , and rx_0 . We claim that if the monomial rx_0 appears in the sum representing m then the privacy property is violated with respect to the player receiving the message, say player P_j . This is because the possible messages that include rx_0 are: rx_0 , $rx_0 \oplus x_0 = (r \oplus 1)x_0$, $rx_0 \oplus x_0 \oplus r = (r \oplus 1)(x_0 \oplus 1) \oplus 1$, and $rx_0 \oplus r = r(x_0 \oplus 1)$ (and their negations). Consider the two input assignments $\bar{e}_{0,j}$ and

295 $\bar{e}_j$. Observe that the distribution of each one of these messages on the inputs $\bar{e}_{0,j}$ and
 296 $\bar{e}_j$ is different, which violates the privacy requirement (“leaking some information” on
 297 x_0 to P_j). For example, rx_0 is always 0 for input $\bar{e}_{0,j}$ and is uniformly distributed for
 298 input $\bar{e}_j$. The argument for the other cases is similar.

299 It follows that the messages sent in round $t = 1$ are either constant or of the
 300 desired form. Since only player P_0 can send non-constant messages in round $t = 1$,
 301 it also follows that by the end of round $t = 1$ each player receives at most a single
 302 non-constant message. Thus, the claim holds for round $t = 1$.

303 We now prove the claim for round $t > 1$, assuming the induction hypothesis holds
 304 for round $t - 1$. Consider player P_i and the message $m_{i,j}^t$ that it sends in round t to
 305 player P_j . Since this message is computed by player P_i at round t , it can be expressed
 306 as a function of x_i , of the single non-constant message m that player P_i received in
 307 some round $t' < t$ (if such a message exists) and, if $i = 0$, of the random bit r . We
 308 distinguish between two cases: when $i \neq 0$, and when $i = 0$.

309 When $i \neq 0$, the message $m_{i,j}^t$ sent by P_i is the sum of a subset of the monomials
 310 $0, 1, x_i, m, mx_i$. We observe the following

311 **OBSERVATION 4.4.** *If the monomial mx_i does not appear in the sum, then $m_{i,j}^t$ is*
 312 *either constant or of the desired form.*

313 *Proof.* If the monomial mx_i does not appear in $m_{i,j}^t$, but $m_{i,j}^t$ is not a constant
 314 and not of the desired form, then $m_{i,j}^t$ is either a useless message, or a message that
 315 violates the privacy property with respect to P_j . This follows by inspection for each
 316 of the 8 subsets of $1, x_i$, and m (represented by $\{0, 1\}^3$ in the natural way): (000,
 317 100) - 0, 1: constants; (010, 110) - $x_i, 1 \oplus x_i$: violates privacy; (001, 101) - $m, 1 \oplus m$:
 318 of the desired form; (011, 111) - $x_i \oplus m, 1 \oplus x_i \oplus m$: of the desired form. $\square$

319 On the other hand, we show in the following that any message defined by any
 320 of the 8 sums of monomials that do include the monomial mx_i violates the privacy
 321 property with respect to P_j , and hence such message cannot be part of π . By the
 322 induction hypothesis $m = r \oplus \sum_{k \in S \subseteq \{0, \dots, n-1\}} x_k$ (or $1 \oplus r \oplus \sum_{k \in S \subseteq \{0, \dots, n-1\}} x_k$), for
 323 some S . Consider the former form, the latter is similar. For the message mx_i (resp.,
 324 $1 \oplus mx_i$) consider the inputs $\bar{e}_{i,j}$ and $\bar{e}_j$ and observe that on the former input the
 325 message is always 0 (resp., 1) while on the latter it is m (resp., $1 \oplus m$), and hence does
 326 not exhibit the same distribution on the two inputs. Similarly, consider the messages
 327 $mx_i \oplus x_i = (m \oplus 1)x_i$, $mx_i \oplus m = m(x_i \oplus 1)$, and $mx_i \oplus x_i \oplus m = (m \oplus 1)(x_i \oplus 1) \oplus 1$
 328 (and their negations), and observe that the message has different distributions on the
 329 inputs $\bar{e}_{i,j}$ and $\bar{e}_j$ (in each of the cases, for one of these two inputs the value of the
 330 message is either m or its negation, i.e., the support of the distribution is of size 2,
 331 and for the other input the distribution has support of size 1).

332 For $i = 0$, player $P_i = P_0$ has also the random bit r , so the message sent by
 333 P_0 at round t to player P_j is the sum of a subset of the monomials $0, 1, x_0, m$,
 334 mx_0, r, rx_0, rm, rmx_0 . But, no non-constant message m can be received by player
 335 P_0 before round t , since any message of the form $r \oplus \sum_{k \in S \subseteq \{0, \dots, n-1\}} x_k$ (or $m =$
 336 $1 \oplus r \oplus \sum_{k \in S \subseteq \{0, \dots, n-1\}} x_k$) would either violate the privacy property (since P_0 knows
 337 r), or would be a useless message: if $S \subseteq \{0\}$ then P_0 can compute the message itself;
 338 if there exists a $k \neq 0, k \in S$, consider the two inputs $\bar{e}_0, \bar{e}_{0,k}$ to see that the privacy
 339 property is violated. It follows that the message sent by player P_0 at round t is either
 340 a constant message or the sum of a subset of the monomials $1, x_0, r, rx_0$. But, we
 341 have proved above (when proving the base case of the induction) that in this case
 342 $m_{i,j}^t$ must be $r \oplus x_0$ (or $1 \oplus r \oplus x_0$).

We conclude that the messages sent in round t are either constant or of the desired form.

Now, assume towards a contradiction that some player P_j receives by the end of round t two non-constant messages which, as we proved above, must be of the desired form. Denote $q_1 = r \oplus \sum_{i \in S_1 \subseteq \{0, \dots, n-1\}} x_i$, and $q_2 = r \oplus \sum_{i \in S_2 \subseteq \{0, \dots, n-1\}} x_i$. The two messages received by player P_j are therefore $m_1 = q_1$ (or $m_1 = 1 \oplus q_1$) and $m_2 = q_2$ (or $m_2 = 1 \oplus q_2$), for some sets S_1 and S_2 . Consider now $Q = m_1 \oplus m_2$. Observe that $Q = \sum_{i \in S' \subseteq \{0, \dots, n-1\}} x_i$ (or $Q = 1 \oplus \sum_{i \in S' \subseteq \{0, \dots, n-1\}} x_i$) for $S' = S_1 \Delta S_2$.

If $S' \subseteq \{j\}$ then, since π is of canonical form, one of the two messages m_1 and m_2 (the one arriving later) cannot exist in π , as it would be a useless message.

For the other case we use the following observation.

OBSERVATION 4.5. *If $S' \not\subseteq \{j\}$, then the privacy property is violated with respect to player P_j .*

Proof. Consider the two inputs $\bar{e}_{j,k}$ and $\bar{e}_j$, for some $k \in S'$, $k \neq j$. These two inputs agree on x_j as well as on the value of the function, but the distributions of the messages that P_j receives on these two inputs are not identical. $\square$

It follows that P_j does not receive two non-constant messages by the end of round t of π , and the claim holds for round t . $\square$

Using the above properties of π we can show that (the assumed) protocol π cannot compute **and**.

LEMMA 4.6. *Consider the protocol π , an arbitrary player P_j and an arbitrary round $t \geq 1$. Then, player P_j cannot compute the function **and** at the end of round t .*

Proof. By Lemma 4.3, player P_j receives by the end of round t at most a single non-constant message, and this message is of the form $m = r \oplus \sum_{i \in S \subseteq \{0, \dots, n-1\}} x_i$ or $m = 1 \oplus r \oplus \sum_{i \in S \subseteq \{0, \dots, n-1\}} x_i$. We distinguish between two cases.

Case 1: For all $k \neq j$, $k \in S$. Since $n \geq 3$, there exist two distinct $k_1, k_2 \in S$, $k_1 \neq j$, $k_2 \neq j$. Consider the two inputs $\bar{1}$ and $\bar{e}_{k_1, k_2}$. While $\mathbf{and}(\bar{1}) \neq \mathbf{and}(\bar{e}_{k_1, k_2})$, the view of P_j at the end of round t is the same on $\bar{1}$ and $\bar{e}_{k_1, k_2}$ and hence π must err on at least one of them (note that this in particular holds when $j = 0$; for all other players, who do not know r , the message m is uniformly distributed).

Case 2: There exists an index $k \neq j$, $k \notin S$. Consider the two inputs $\bar{1}$ and $\bar{e}_k$. As in Case 1, π must err on at least one of these inputs. $\square$

We conclude that protocol π (a 1-random private protocol for **and**) does not exist.

THEOREM 4.7. *The private computation of the function **and**, with $n \geq 3$ players, cannot be performed using a single random bit.*

5. Upper Bounds. In this section, we provide significantly improved upper bounds on the randomness complexity of **and**. Specifically, we show that **and** on any number of players n can be privately computed using 8 random bits, and can be computed with 7 random bits for the special case of $n = 3$ players. This is compared to the previously best upper bound of 73 implicit in [19].

In order to present our protocol, we first present two building blocks which are used in our constructions. They are both implementations of information-theoretic 1-out-of-2 Oblivious Transfer.

5.1. 1-out-of-2 Oblivious Transfer. In a 1-out-of-2 Oblivious Transfer (1-2 OT) protocol two parties, Alice and Bob, engage in a protocol that allows Bob to choose which part of the information that Alice holds he wants to learn, in such a

way that Alice does not learn which part of her information Bob learned and Bob learns nothing about the other part.

More formally, for a 1-out-of-2 (bit) Oblivious Transfer protocol Alice has two bits b_0 and b_1 , and Bob has a selection bit s . Alice and Bob, together with a set of helper players, $\mathcal{H}$, engage in a protocol at the end of which the following holds:

- Bob knows the value of b_s .
- Bob does not learn any information on $b_{1 \oplus s}$ (i.e., the transcript of Bob, given the values of s and b_s , is identically distributed whether the bit $b_{1 \oplus s}$ is 0 or 1).
- Alice does not learn anything (i.e., the transcript of Alice, given any choice of values for b_0 and b_1 , is identically distributed; in particular, it is independent of s).
- The helper players $\mathcal{H}$ do not learn anything (i.e., the transcript of each of them is distributed independently of the inputs s, b_0, b_1).

We now give two implementations of this building block. The difference between the two implementations is in that one requires less random bits than the other, but requires more, two instead of one, “helper” players. Both implementations are used in our protocols. If the number of players is odd, the first implementation suffices (we still have two helper players overall, but in each OT invocation only one of them is used). We use the latter implementation for our protocol for number of players $n \geq 4$, even if not odd, where we want to save in random bits in spite of the fact that we need to use a separate OT protocol for the last player (see Section 5.2.2).

5.1.1. Implementation 1: 3 random bits, 1 helper player.. This implementation is given by Beaver [2].

There is one helper player, denoted by H . The protocol is defined as follows.

1. The helper player H tosses 2 uniformly distributed and independent random bits, r_0 and r_1 (to be used as masking bits), and one additional independent and uniformly distributed random bit p (to define one of the two possible permutations of $\{0, 1\}$).
2. H sends both r_0 and r_1 to Alice and it sends p and $r^* = r_p$ to Bob.
3. Bob sends to Alice the message $i = s \oplus p$.
4. Alice sends to Bob the two bits $m_0 = b_0 \oplus r_i$ and $m_1 = b_1 \oplus r_{1 \oplus i}$.
5. Bob “deciphers” the value of the bit he wants to learn (i.e., b_s) by computing $m_s \oplus r^*$.

The fact that Bob learns the value of b_s follows by simple case analysis ($p = 0$ or $p = 1$).

For completeness, we sketch a proof of the privacy of this protocol. A more detailed formal proof is incorporated within the privacy proof for our protocol that uses the OT protocol as a sub-protocol. We observe the following:

- H does not receive any message and hence privacy is preserved with respect to H .
- Alice receives from H the bits r_0 and r_1 and from Bob the bit $i = s \oplus p$. All three are independent and uniformly distributed between 0 and 1 (as r_0, r_1 , and p are uniformly distributed and independent random bits).
- Bob receives from H the bits p and $r^* = r_p$ (but not the bit $r_{1 \oplus p}$), and from Alice the bits $m_0 = b_0 \oplus r_i$ and $m_1 = b_1 \oplus r_{1 \oplus i}$. Observe that $b_s = m_s \oplus r^*$, but p and $m_{1 \oplus s}$ are both independent of m_s and r^* , and uniformly distributed.

5.1.2. Implementation 2: 2 random bits, 2 helper players.. To the best of our knowledge, the following simple implementation of information theoretic 1-out-

of-2 OT did not previously appear in the literature.

Here we assume that there are two helper players, denoted H_0 and H_1 . The protocol is defined as follows.

1. Alice tosses two independent random bits p and r .
2. Alice sends the message $m_0 = b_0 \oplus r$ to player H_p , the message $m_1 = b_1 \oplus r$ to player $H_{1 \oplus p}$, and p and r to Bob.
3. Bob sends the bit 1 to player $H_{s \oplus p}$ and the bit 0 to player $H_{1 \oplus s \oplus p}$.
4. If player H_0 (resp., H_1) receives 1 from Bob, it sends to Bob the message m it received from Alice (i.e., either m_0 or m_1). Otherwise, if player H_0 (resp., H_1) receives 0 from Bob, it sends to Bob the (constant) message 0.⁷
5. Bob “deciphers” the value of the bit he wants to learn (i.e., b_s) by computing $b_s = m \oplus r$, where m is the message Bob got from $H_{s \oplus p}$.

The fact that Bob learns the value of b_s follows from the protocol, by inspection. For completeness, we sketch a proof of the privacy of this protocol. A more detailed formal proof is incorporated within the privacy proof for our protocol that uses the OT protocol as a sub-protocol. We observe the following:

- Alice does not get any message and hence privacy is preserved with respect to Alice.
- Each of H_0 and H_1 gets a single message from Alice, which is one of her input bits xored with r ; it also received from Bob a bit which is either 0 or 1, depending on the value $s \oplus p$; since r and p are uniformly random and independent, then privacy is preserved with respect to each one of the helper players H_0 and H_1 .
- Bob receives p and r from Alice. Then, given the value of p and the value of s , known to Bob, it receives a constant message from one of H_0 or H_1 , and the message $b_s \oplus r$ from the other (if $s \oplus p = 1$ Bob receives the constant message from H_0 , and if $s \oplus p = 0$ Bob receives the constant message from H_1 .) Hence, given the value of b_s , the transcript of Bob is distributed uniformly.

5.2. The and protocol. We first present a protocol, Π_{odd} , applicable to an odd number of players; this protocol uses 8 random bits. This protocol serves to introduce the main ideas of our protocols, and is also the basis for a somewhat improved protocol for $n = 3$, that uses 7 random bits. The case of an odd number of players is easier than the case of an even number of players because if one uses one helper player for the OT protocols performed by pairs of players (P_{2j}, P_{2j+1}) , and another helper player for the OT protocols performed by pairs of players $(P_{2j+1}, P_{2(j+1)})$, then the two extreme pairs do not use the same helper player. Therefore, these helper players can be players P_0 and P_{n-1} , which participate each in a single OT protocol. This is not the case when the number of players is even. Extending Π_{odd} to work also for even number of players and keeping the 8 random bits bound requires therefore some more effort, and we give such a protocol in Subsection 5.2.2, applicable to any $n \geq 4$.

5.2.1. Odd number of players. We describe our protocol Π_{odd} for odd number of players, n , denoted $P_0, P_1, \dots, P_{n-1}$.

initialization phase. In the initialization phase player P_0 tosses 3 random bits and

⁷Clearly in this case the relevant helper player does not need to send any message to Bob. However in order to stay coherent with the model we use, we define which bit is sent in each round between any two players, unless for all inputs and all random coins values, no message is sent between the two.

plays the role of the helper player of implementation 1 of *OT* for all pairs of players where Alice is an odd player and Bob is the successive even player. Player P_{n-1} does the same for all pairs of players where Alice is an even player and Bob is the successive odd player. Specifically:

Player P_0 tosses 3 random bits r_0^0 , r_1^0 , and p^0 . It sends the bits r_0^0 , r_1^0 to all odd players, and sends the bits p^0 and $r_{p^0}^0$ to all even players.

Player P_{n-1} tosses 3 random bits r_0^1 , r_1^1 , and p^1 . It sends the bits r_0^1 , r_1^1 to all even players, and sends the bits p^1 and $r_{p^1}^1$ to all odd players.

In addition, player P_0 tosses 2 additional random bits q_0 and q_1 . It sends q_0 to all even players, and q_1 to all odd players. P_0 also locally computes $y_0 = q_0 \oplus q_1 \oplus x_0$.

computation phase. This phase runs in $n - 1$ rounds. The inductive invariant that we maintain is that at the end of round $i \geq 1$ player P_i has the value $y_i = q_0 \oplus q_1 \oplus \Pi_{j=0}^i x_j$. In each round, the protocol will run an *OT* protocol. We give a detailed description of the rounds below.

final phase. At the end of the computation phase, player P_{n-1} has (by the inductive invariant) the value $y_{n-1} = q_0 \oplus q_1 \oplus \Pi_{j=0}^{n-1} x_j$. It sends this value to P_0 who xors it with $q_0 \oplus q_1$ to obtain $\Pi_{j=0}^{n-1} x_j = \text{and}(x_0, x_1, \dots, x_{n-1})$. Player P_0 then sends this value to all other players.

We now define how the computation phase is implemented so as to maintain the inductive invariant (and privacy, as we prove later). The invariant clearly holds at the end of round 0 (i.e., before the computation phase starts) since player P_0 has x_0 , q_0 , and q_1 and hence can compute y_0 .

Now, in round $i \geq 1$ players P_{i-1} and P_i engage in a 1-2 *OT* protocol, using Implementation 1 described above. The values that Alice (i.e., player P_{i-1}) holds for the *OT* protocol are $b_0 = q_{(i-1) \bmod 2}$ and $b_1 = y_{i-1}$. Observe that Alice has b_0 from the initialization phase, and b_1 by the inductive invariant. The selection bit of Bob (i.e., player P_i) is $s = x_i$. The random bits used for the *OT* protocol are r_0^k , r_1^k , and p^k , where $k = i \bmod 2$. Observe that P_i and P_{i-1} receive in the initialization phase the random bits needed in order to simulate Alice and Bob of the *OT* protocol (i.e., r_0^k , r_1^k for Alice and p^k , $r_{p^k}^k$ for Bob). Let v_i denote the output (i.e., the bit learned by Bob) of the *OT* protocol run in the i -th round.

It follows that at the end of the *OT* protocol, if the value that player P_i holds is $x_i = 0$, then it gets from player P_{i-1} the value $v_i = q_{(i-1) \bmod 2}$, and if $x_i = 1$ then it gets the value $v_i = y_{i-1} = q_0 \oplus q_1 \oplus \Pi_{j=0}^{i-1} x_j$.

Now, if $x_i = 0$ then $\Pi_{j=0}^i x_j = 0$, and player P_i has y_i by calculating $q_{(i-1) \bmod 2} \oplus q_{i \bmod 2}$, where the former is just v_i and the latter is received from P_0 in the initialization phase.

If $x_i = 1$ then $\Pi_{j=0}^i x_j = \Pi_{j=0}^{i-1} x_j$ and player P_i just sets $y_i = v_i$.

The total number of random bits used in this protocol is 8: the protocol uses 3 bits for each of the two sets of *OT* protocols, and 2 additional masking bits, q_0 and q_1 .

It remains to prove that privacy is preserved with respect to all players. Intuitively, there are $n - 1$ invocations of the *OT* protocol. Each internal player (i.e., all players except P_0 and P_{n-1}) participates in two *OT* invocations, once as Alice (with the following player) and once as Bob (with the preceding player), each of these two invocations using different sets of random bits, one set from P_0 and one set from P_{n-1} . Players P_0 and P_{n-1} participate each in a single invocation of the *OT* protocol, P_0 as Alice with P_1 and P_{n-1} as Bob with P_{n-2} . Hence the number of players must be

odd (to guarantee that the random bits used by the *OT* protocol of P_{n-1} and P_{n-2} come from P_0 and not from P_{n-1}). Formally,

THEOREM 5.1. *The and protocol Π_{odd} is private for n odd, $n \geq 3$.*

Proof. We first prove the claim for players P_i , $0 < i < n - 1$, and then for P_0 and for P_{n-1} .

For $0 < i < n - 1$, observe that player P_i receives messages pertaining to exactly two *OT* invocations, one in which it plays the role of Alice, and one where it plays the role of Bob. In addition, P_i receives from player P_0 either the bit q_0 or the bit q_1 and, at the end of the protocol, the computed value of the function.

We prove the claim for i even (the case of i odd is analogous, switching the roles of the random bits, i.e., flipping their superscripts, and switching between q_0 and q_1). The messages that such player P_i receives are:

1. During the initialization phase: bits $r_0^1, r_1^1, p^0, r_{p^0}^0, q_0$.
2. During the *OT* protocol with player P_{i-1} (i.e., when playing the role of Bob):
 - $q_1 \oplus r_j^0$ and $y_{i-1} \oplus r_{1 \oplus j}^0$, where $j = x_i \oplus p^0$.
3. During the *OT* protocol with player P_{i+1} (i.e., when playing the role of Alice):
 - $x_{i+1} \oplus p^1$.
4. In the final phase, from player P_0 , $\text{and}(x_0, x_1, \dots, x_{n-1})$.

Observing the nine messages received by P_i , one can verify that:

1. The messages received in Stage 1 are just the random bits $r_0^1, r_1^1, p^0, r_{p^0}^0, q_0$.
2. For the messages of Stage 2 we distinguish between two cases depending on the value of x_i .
 If $x_i = 0$ then $j = p^0$ and the first message is $q_1 \oplus r_{p^0}^0$ and the second one is $y_{i-1} \oplus r_{1 \oplus p^0}^0$. We have that the first message includes an **xor** operation with q_1 , and the second one an **xor** with $r_{1 \oplus p^0}^0$.
 If $x_i = 1$ then the first message is $q_1 \oplus r_{1 \oplus p^0}^0$ and the second one is $y_{i-1} \oplus r_{p^0}^0$. In that case, the first message includes an **xor** operation with $r_{1 \oplus p^0}^0$ and the second one an **xor** with q_1 (since by the inductive invariant, $y_{i-1} = q_0 \oplus q_1 \oplus \Pi_{j=0}^{i-1} x_j$).
3. The message received in Stage 3 includes an **xor** operation with p^1 .
4. The message received in Stage 4 is the value of the function.

Inspecting the distribution of the above messages, the last message (Stage 4) is, by definition, the value of the function; all other 8 messages are independent and uniformly distributed (in correspondence with the 8 random bits that are used): the bits $r_0^1, r_1^1, p^0, r_{p^0}^0, q_0$ in Stage 1, the two messages of Stage 2 one includes an **xor** operation with $r_{1 \oplus p^0}^0$ and the other with q_1 , and the message received in Stage 3 which includes an **xor** operation with p^1 . Hence, the privacy with respect to P_i follows.

Almost the same argument applies to player P_{n-1} as well. It receives a subset of the messages received by players P_i , $0 < i < n - 1$, namely, those of Stages 1, 2, 4 above (note that $n - 1$ is even). In addition it knows the value of the random bit p^1 . But, since the message of Stage 3 is not received by P_{n-1} , the privacy with respect to P_{n-1} holds.

As to player P_0 , it receives the messages listed under Stages 1 and 3 above (again, P_0 is an even player), and from player P_{n-1} at the final phase the message $y_{n-1} = q_0 \oplus q_1 \oplus \Pi_{j=0}^{n-1} x_j$. In addition, player P_0 knows the values of the random bits r_0^0, r_1^0, q_0 and q_1 . We have that the messages received in Stages 1 and 3 each includes an **xor** operation with an independent (uniformly distributed) random bit not known to P_0 .

The value of the message received in the final phase is determined by the value of the function, q_0 and q_1 . Hence, privacy with respect to player P_0 holds as well. $\square$

5.2.2. At least 4 players. If one attempts to apply the above protocol Π_{odd} to an even number of players then privacy will not be preserved. This is because when players P_{n-2} and P_{n-1} engage in their OT protocol, they will do that with the random bits tossed by player P_{n-1} which will be able to learn both bits of P_{n-2} (while in the case of odd n the random bits for the last pair are tossed by the “helper” P_0).

To remedy this problem, we stop the computation phase one round earlier, that is, we run it for $n - 2$ rounds only, at the end of which player P_{n-2} has, as in Π_{odd} , the value $y_{n-2} = q_0 \oplus q_1 \oplus \Pi_{j=0}^{n-2} x_j$. We then perform the last OT protocol of the computation phase using Implementation 2 defined above and fresh random bits. This, however, increases the total number of random bits used, and further requires that the total number of players is at least 4 (as required by Implementation 2 of OT).

While requiring at least 4 players is not an issue since we have another variant of the protocol for odd number of players, in order not to increase the total number of random bits used, we generate and distribute the random bits needed for the various OT invocations in a more efficient way. That is, while each internal player still participates in 2 OT invocations, we do not need totally separate 2 sets of 3 random bits, as we do in Π_{odd} . Rather, it is sufficient to ensure that no player will receive two messages (of two different OT invocations) that “use” the same random bit. We thus generate the sets of 3 random bits needed for each invocation of the OT protocol (implementation 1) in a more sophisticated way, which is based on 4 true random bits rather than on 6 as in the straightforward manner used in Π_{odd} . The resulting protocol uses a total of 8 random bits and is applicable to any $n \geq 4$.

We now formally describe our protocol for $n \geq 4$ players, denoted $P_0, P_1, \dots, P_{n-1}$. As indicated above, the high level structure of the protocol is the same as that of Π_{odd} , with some modifications, most notably a different way to produce and distribute the random bits.

initialization phase. In the initialization phase player P_{n-1} tosses 4 random bits u_0, u_1, u_2, u_4 and defines a sequence of bits $r_0, r_1, \dots, r_\ell$, for $\ell = 2(n - 2)$, recursively as follows:⁸

$r_0 = u_0, r_1 = u_1, r_2 = u_2, r_4 = u_4$, and

$$(5.1) \quad r_j = \begin{cases} r_{j-3+r_{j-1}} & j > 1, j \text{ odd} \\ r_{j-6+(1 \oplus r_{j-4})} & j > 4, j \text{ even} \end{cases}.$$

Player P_{n-1} then sends to each player P_i , $0 \leq i \leq n - 2$ the two bits r_{2i}, r_{2i+1} .

In addition, player P_0 tosses 2 additional random bits q_0 and q_1 . It sends q_0 to all odd players, and q_1 to all even players. P_0 also locally computes $y_0 = q_0 \oplus q_1 \oplus x_0$.

computation phase. This phase runs in $n - 1$ rounds. The inductive invariant that we maintain is that at the end of round $i \geq 1$ player P_i has the value $y_i = q_0 \oplus q_1 \oplus \Pi_{j=0}^i x_j$. In each round, the protocol will run an OT protocol. We give a detailed description of the rounds below.

final phase. At the end of the computation phase, player P_{n-1} has (by the inductive invariant) the value $y_{n-1} = q_0 \oplus q_1 \oplus \Pi_{j=0}^{n-1} x_j$. It sends this value to P_0 who xors

⁸Here and in the following we sometimes abuse notation and consider indices that involve summations over both $\mathcal{N}$ and $\mathcal{F}_2$ (denoted with the operands $+$ and $\oplus$, respectively). For example, in the expression $r_{j-6+(1 \oplus r_{j-4})}$ in Eq (5.1), the subscript should be parsed as follows: first evaluate $1 \oplus r_{j-4}$ over $\mathcal{F}_2$, to get a value in $\{0, 1\}$, and then add this value to $j - 6$ over the integers.

it with $q_0 \oplus q_1$ to obtain $\Pi_{j=0}^{n-1} x_j = \text{and}(x_0, x_1, \dots, x_{n-1})$. Player P_0 then sends this value to all other players.

The following claim gives the properties of the sequence of bits r_j , necessary both for the correctness of the protocol and for its privacy. The proof of this claim is quite technical and the reader may wish to skip this proof.

CLAIM 5.2. *For any $1 \leq i \leq n - 2$, the five bits r_j , $2(i - 1) \leq j \leq 2(i + 1)$, are such that*

1. $r_{2i+1} = r_{2(i-1)+r_{2i}}$.
2. *The four bits $r_{2(i-1)}, r_{2(i-1)+1}, r_{2i}, r_{2(i+1)}$ are independent and uniformly distributed.*

Proof. We prove the claim by induction on i . For the base of the induction ($i = 1$), observe that Point (2) is satisfied since r_0, r_1, r_2, r_4 are set to be u_0, u_1, u_2, u_4 , respectively, and these are independent and uniformly distributed random bits tossed by Player P_{n-1} . As to Point (1), r_3 is set to be equal to r_{r_2} according to Equation (5.1) (first part, with $j = 3$).

We now prove the claim for $i + 1$ assuming it is correct for i . Note that the 5-tuple that corresponds to $i + 1$ partially overlaps the 5-tuple that corresponds to i .

Point (1) holds for $i + 1$ because by the first part of Equation (5.1) (taking j to be $2(i + 1) + 1$) $r_{2(i+1)+1} = r_{2i+1+r_{2(i+1)}}$.

As to Point (2), we consider both parts of Equation (5.1) and the value of r_{2i} . There are two cases:

1. If $r_{2i} = 0$:
 - $r_{2i+1} = r_{2(i-1)}$ (taking $j = 2i + 1$ for the first part of Equation (5.1)).
 - $r_{2(i+2)} = r_{2(i-1)+1}$ (taking $j = 2(i + 2)$ for the second part of Equation (5.1)).
2. If $r_{2i} = 1$:
 - $r_{2i+1} = r_{2(i-1)+1}$ (taking $j = 2i + 1$ for the first part of Equation (5.1)).
 - $r_{2(i+2)} = r_{2(i-1)}$ (taking $j = 2(i + 2)$ for the second part of Equation (5.1)).

It follows that the 4-tuple of bits with indices $2i, 2i+1, 2(i+1)$ and $2(i+2)$, i.e., the 4-tuple $(r_{2i}, r_{2i+1}, r_{2(i+1)}, r_{2(i+2)})$ is equal to either the 4-tuple $(r_{2i}, r_{2(i-1)}, r_{2(i+1)}, r_{2(i-1)+1})$ (if $r_{2i} = 0$) or to $(r_{2i}, r_{2(i-1)+1}, r_{2(i+1)}, r_{2(i-1)})$ (if $r_{2i} = 1$), which are two permutations of the same 4 bits. By the induction hypothesis, these 4 bits are independent and uniformly distributed. Hence also Point (2) holds for $i + 1$. $\square$

We now define how the computation phase is implemented so as to maintain the inductive invariant which is that at the end of round $i \geq 1$ player P_i has the value $y_i = q_0 \oplus q_1 \oplus \Pi_{j=0}^i x_j$ (and so as to preserve privacy, as we prove later). The invariant clearly holds at the end of round 0 (i.e., before the computation phase starts) since player P_0 has x_0, q_0 , and q_1 and hence can compute y_0 .

Similarly to protocol Π_{odd} , in round $1 \leq i \leq n - 2$ (but not in round $n - 1$, as is the case for Π_{odd}) players P_{i-1} and P_i engage in a 1-2 *OT* protocol, using Implementation 1 described above. The values that Alice (i.e., player P_{i-1}) holds for the *OT* protocol are $b_0 = q_i \bmod 2$ and $b_1 = y_{i-1}$. Observe that Alice has b_0 from the initialization phase, and b_1 by the inductive invariant. The selection bit of Bob (i.e., player P_i) is $s = x_i$. The random bits used for the *OT* protocol are $r_{2(i-1)}$ and $r_{2(i-1)+1}$ held by Alice (player P_{i-1}) and r_{2i} held by Bob (player P_i). Observe that P_i and P_{i-1} receive these bits from P_{n-1} during the initialization phase. Further, by Claim 5.2 the bits $r_{2(i-1)}$ and $r_{2(i-1)+1}$, held by player P_{i-1} , and the bit r_{2i} , held by

player P_i , all satisfy the properties required for the OT protocol to be correct (and private).

Finally, in round $i = n - 1$, players P_{n-2} and P_{n-1} engage in an OT protocol as in previous rounds, but using Implementation 2 and using additional new random bits.⁹ Specifically, P_{n-1} is Bob of the OT protocol and P_{n-2} is Alice; the helper players are P_0 (H_0) and P_1 (H_1), and we denote the two fresh random bits tossed by P_{n-2} by u_5 and u_6 (see Section 5.1.2). The use of Implementation 2 of the OT protocol in this round is the reason that the protocol described here works only for $n \geq 4$.

As in protocol Π_{odd} , let v_i denote the output (i.e., the bit learned by Bob) of the OT protocol run in the i -th round, $1 \leq i \leq n - 1$. It follows that at the end of the OT protocol, if the value that player P_i holds as input is $x_i = 0$, then it gets from player P_{i-1} the value $v_i = q_i \bmod 2$, and if $x_i = 1$ it gets the value $v_i = y_{i-1} = q_0 \oplus q_1 \oplus \Pi_{j=0}^{i-1} x_j$.

Now, if $x_i = 0$ then $\Pi_{j=0}^i x_j = 0$, and player P_i has y_i by calculating $q_i \bmod 2 \oplus q_{(i+1) \bmod 2}$, where the former is just v_i and the latter is received from P_0 in the initialization phase. If $x_i = 1$ then $\Pi_{j=0}^i x_j = \Pi_{j=0}^{i-1} x_j$ and player P_i just sets $y_i = v_i$.

The total number of random bits used in this protocol is 8: u_0, u_1, u_2, u_4 and q_0, q_1 are tossed by player P_0 , and u_5, u_6 are tossed by player P_{n-2} .

It remains to prove that privacy is preserved with respect to all players. Intuitively, there are $n - 1$ invocations of the OT protocol. Each internal player (i.e., all players except P_0 and P_{n-1}) participates in two OT invocations, once as Alice and once as Bob. All players, except $P_0, P_1, P_{n-2}, P_{n-1}$, only participate in these two OT invocations, and the privacy property with respect to those players will follow from the properties of the sequence of bits r_j (Claim 5.2). Players $P_0, P_1, P_{n-2}, P_{n-1}$ also participate in the invocation of the last OT invocation using Implementation 2, either as Alice or Bob or as helper players, and player P_0 also receives in the last phase of the protocol a message from which it can deduce the value of the function. The privacy with respect to those players will follow from the privacy of the two implementations of the OT primitive and from the specific random bits used. We now formally prove that the protocol is private.

THEOREM 5.3. *The and protocol for $n \geq 4$ is private.*

Proof. We first prove the claim for players P_i , $1 < i < n - 2$, and then for the players having special roles, $P_0, P_1, P_{n-2}, P_{n-1}$.

For $1 < i < n - 2$, observe that player P_i receives messages pertaining to exactly two OT invocations, one in which it plays the role of Alice, and one where it plays the role of Bob (as implemented in Section 5.1.1). In addition, P_i receives from player P_0 either the bit q_0 or the bit q_1 and, at the end of the protocol, the computed value of the function.

We prove the claim for i even (the case of i odd is analogous, switching the roles of q_0 and q_1). The messages player P_i receives are:

1. During the initialization phase: bits r_{2i}, r_{2i+1}, q_0 .
2. During the OT protocol with player P_{i-1} (i.e., when playing the role of Bob):
 - $q_1 \oplus r_{2(i-1)+j}$ and $y_{i-1} \oplus r_{2(i-1)+(1 \oplus j)}$, where $j = x_i \oplus r_{2i}$.
3. During the OT protocol with player P_{i+1} (i.e., when playing the role of Alice):
 - $x_{i+1} \oplus r_{2(i+1)}$.

⁹It is also possible to perform the OT protocol of this round using Implementation 1 with a separate set of 3 random bits, tossed by another player, say player P_0 , but this results in a larger total number of random bits for the protocol.

4. In the final phase, from player P_0 , $\text{and}(x_0, x_1, \dots, x_{n-1})$.

Observing the seven messages received by P_i , one can verify that:

1. The messages received in Stage 1 are the bits r_{2i}, r_{2i+1}, q_0 .
2. For the messages of Stage 2, we distinguish between two cases depending on the value of x_i .
 If $x_i = 0$ then the first message is $q_1 \oplus r_{2(i-1)+r_{2i}}$ and the second one is $y_{i-1} \oplus r_{2(i-1)+(1 \oplus r_{2i})}$. In this case, the first message includes an **xor** operation with q_1 , and the second one an **xor** operation with $r_{2(i-1)+(1 \oplus r_{2i})}$.
 If $x_i = 1$ then the first message is $q_1 \oplus r_{2(i-1)+(1 \oplus r_{2i})}$ and the second one is $y_{i-1} \oplus r_{2(i-1)+r_{2i}}$. In this case, the first message includes an **xor** operation with $r_{2(i-1)+(1 \oplus r_{2i})}$ and the second one an **xor** operation with q_1 (since by the inductive invariant, $y_{i-1} = q_0 \oplus q_1 \oplus \prod_{j=0}^{i-1} x_j$).
3. The message received in Stage 3 includes an **xor** operation with $r_{2(i+1)}$.
4. The message received in Stage 4 is the value of the function.

The last message (Stage 4) is, by definition, the value of the function. From the observations above, it follows that the distribution of the other 6 messages is the same as the distribution of the tuple $r_{2i}, r_{2i+1}, q_0, q_1, r_{2(i-1)+(1 \oplus r_{2i})}, r_{2(i+1)}$ (if $x_i = 0$) or the tuple $r_{2i}, r_{2i+1}, q_0, r_{2(i-1)+(1 \oplus r_{2i})}, q_1, r_{2(i+1)}$ (if $x_i = 1$). But, using Claim 5.2, we can conclude that both of these 6-tuples are uniformly distributed over the 2^6 possible binary vectors. Thus, privacy is preserved for all players P_i , $1 < i < n - 2$.

Similar arguments apply to the remaining four players. Let $\hat{b}_0 = q_{(n-1) \bmod 2} \oplus u_6$ and let $\hat{b}_1 = y_{n-2} \oplus u_6$ (recall that player P_{n-2} tosses two random bits u_5, u_6 , to be used by the *OT* protocol, Implementation 2, in round $n - 1$).

Player P_0 : Player P_0 receives the following messages: those listed under Stages 1 and 3 above; in round $n - 1$ of the computation phase, when Implementation 2 of *OT* is invoked, P_0 receives from P_{n-2} either the message $\hat{b}_0 = q_{n-1 \bmod 2} \oplus u_6$ or the message $\hat{b}_1 = y_{n-2} \oplus u_6$ and from P_{n-1} the message $x_{n-1} \oplus u_5 \oplus 1$; and from P_{n-1} , at the final phase, the message $y_{n-1} = q_0 \oplus q_1 \oplus \prod_{j=0}^{n-1} x_j$. In addition, player P_0 has the values of the random bits q_0 and q_1 tossed by itself. Therefore, the messages received in Stages 1 and 3, as well as the messages received from P_{n-2} and P_{n-1} , each includes an **xor** operation with an independent (uniformly distributed) random bit not known to P_0 . The message received in the final phase is (together with q_0 and q_1) the value of the function. Hence, privacy with respect to P_0 holds.

Player P_1 : Player P_1 receives the following messages: the messages listed under Stages 1, 3 and 4 above; In round $n - 1$ of the computation phase, when Implementation 2 of *OT* is invoked, P_1 receives from P_{n-2} either the message $\hat{b}_0 = q_{n-1 \bmod 2} \oplus u_6$ or the message $\hat{b}_1 = y_{n-2} \oplus u_6$ and from P_{n-1} the message $x_{n-1} \oplus u_5$. Therefore, the messages received in Stages 1 and 3, as well as the messages received from P_{n-2} and P_{n-1} , each includes an **xor** operation with an independent (uniformly distributed) random bit not known to P_1 . The message received in Stage 4 is the value of the function. Hence privacy with respect to P_1 holds.

Player P_{n-2} : The set of messages that player P_{n-2} receives is a subset of the messages received by players P_i , $1 < i < n - 2$. None of these messages depend on u_5 or u_6 tossed by P_{n-2} . The privacy with respect to player P_{n-2} thus follows from the proof for P_i , $1 < i < n - 2$.

Player P_{n-1} : Player P_{n-1} receives a subset of the messages received by the players P_i , $1 < i < n - 2$, namely those of Stage 1 and of Stage 4. In addition, it receives, while engaging in Implementation 2 of the *OT* protocol with player P_{n-2} and helpers P_0, P_1 , the following messages:

(1) the messages u_5 and u_6 from player P_{n-2} ,
 (2) the message $M_0 \cdot (x_{n-1} \oplus u_5 \oplus 1)$ from player P_0 , where M_0 is the message P_0 receives from P_{n-2} in the OT protocol, Implementation 2,
 (3) the message $M_1 \cdot (x_{n-1} \oplus u_5)$ from player P_1 , where M_1 is the message P_1 receives from P_{n-2} in the OT protocol, Implementation 2.
 We now have four cases depending on the values of x_{n-1} and u_5 . In each of the four cases, the two messages received from P_0 and P_1 can be written as follows:

- $x_{n-1} = 0, u_5 = 0$: P_{n-1} receives from P_1 the message 0, and from P_0 the message $M_0 = \hat{b}_0 = q_{(n-1) \bmod 2} \oplus u_6$.
- $x_{n-1} = 0, u_5 = 1$: P_{n-1} receives from P_0 the message 0, and from P_1 the message $M_1 = \hat{b}_0 = q_{(n-1) \bmod 2} \oplus u_6$.
- $x_{n-1} = 1, u_5 = 0$: P_{n-1} receives from P_0 the message 0, and from P_1 the message $M_1 = \hat{b}_1 = y_{n-2} \oplus u_6$.
- $x_{n-1} = 1, u_5 = 1$: P_{n-1} receives from P_1 the message 0, and from P_0 the message $M_0 = \hat{b}_1 = y_{n-2} \oplus u_6$.

It can be verified that, given the values of x_{n-1} and of $\mathbf{and}(x_0, x_1, \dots, x_{n-1})$, the distribution of the messages received by P_{n-1} is identical in all four cases. Indeed, given the value x_{n-1} , the value of u_5 determines which of the two messages above is a constant, and which includes an $\mathbf{xor}$ operation with $q_{(n-1) \bmod 2}$. Now recall that $y_{n-2} = q_0 \oplus q_1 \oplus \Pi_{j=0}^{n-2} x_j$, thus the rest of the messages (except $\mathbf{and}(x_0, x_1, \dots, x_{n-1})$) include an $\mathbf{xor}$ operation with a distinct random bit, other than $q_{(n-1) \bmod 2}$, all are uniformly distributed and independent. Hence, privacy is preserved with respect to P_{n-1} . $\square$

5.2.3. The case of $n = 3$. This case can be slightly improved compared to the general case. We can privately compute the $\mathbf{and}$ of 3 players using 7 random bits instead of 8.

The protocol is simple to define: run the protocol Π_{odd} , but fix the bit q_1 to be 0 (rather than it being a random bit).

The correctness of the protocol clearly holds since it holds for Π_{odd} with any choice of random bits. To see that privacy is still preserved with respect to all three players, observe that both player P_0 and player P_1 get q_1 in the original protocol (P_0 tosses it, and P_1 gets it in the initialization phase). Therefore, fixing it to 0 leaves the privacy with respect to these two players intact. As to player P_2 , note that the OT protocol performed between P_1 and P_2 does not change in the modified protocol. Therefore, if $x_2 = 0$ then P_2 gets q_1 (which is fixed to 0), and no other information. If $x_2 = 1$ then the only information P_2 gets is $q_0 \oplus q_1 \oplus \Pi_{j=0}^1 x_j = q_0 \oplus \Pi_{j=0}^1 x_j$, from which it can compute, using the bit q_0 that it got in the initialization phase, the value of $\Pi_{j=0}^1 x_j$. But this value can be inferred, in the case of $n = 3$ and $x_2 = 1$ from the value of the function and x_2 , so privacy is preserved with respect to P_2 too.

6. Conclusions. We consider the randomness complexity of the information-theoretic multi-party private computation of the function $\mathbf{and}$. We show that this computation cannot be done using a single random bit, thus giving the first non-trivial lower bound on the randomness complexity of the private computation of an explicit boolean function. We further give an improved upper bound on the randomness complexity of the private computation of $\mathbf{and}$, thus approaching the exact determination of that measure for $\mathbf{and}$. To the best of our knowledge, for no explicit function f is the exact randomness complexity of the private computation of f known (except for $\mathbf{xor}$, which is trivially 1-random, and degenerate functions). We leave the

exact determination of the randomness complexity of private computations of **and** for further research.

Acknowledgements. We would like to thank an anonymous reviewer of an earlier version of this paper for comments which helped us reduce the upper bound for even number of players from 10 random bits to 8 random bits, and hence also the general upper bound from 10 to 8.

REFERENCES

- [1] G. ASHAROV AND Y. LINDELL, *A full proof of the BGW protocol for perfectly secure multiparty computation*, J. Cryptology, 30 (2017), pp. 58–151, <https://doi.org/10.1007/s00145-015-9214-4>, <https://doi.org/10.1007/s00145-015-9214-4>.
- [2] D. BEAVER, *Precomputing oblivious transfer*, in Advances in Cryptology - CRYPTO '95, 15th Annual International Cryptology Conference, Santa Barbara, California, USA, August 27–31, 1995, Proceedings, 1995, pp. 97–109, https://doi.org/10.1007/3-540-44750-4_8, http://dx.doi.org/10.1007/3-540-44750-4_8.
- [3] M. BEN-OR, S. GOLDWASSER, AND A. WIGDERSON, *Completeness theorems for non-cryptographic fault-tolerant distributed computation (extended abstract)*, in Proceedings of the 20th Annual ACM Symposium on Theory of Computing, May 2–4, 1988, Chicago, Illinois, USA, 1988, pp. 1–10, <https://doi.org/10.1145/62212.62213>, <http://doi.acm.org/10.1145/62212.62213>.
- [4] C. BLUNDO, C. GALDI, AND P. PERSIANO, *Randomness recycling in constant-round private computations (extended abstract)*, in Distributed Computing, 13th International Symposium, Bratislava, Slovak Republic, September 27–29, 1999, Proceedings, P. Jayanti, ed., vol. 1693 of Lecture Notes in Computer Science, Springer, 1999, pp. 138–150, https://doi.org/10.1007/3-540-48169-9_10, https://doi.org/10.1007/3-540-48169-9_10.
- [5] C. BLUNDO, A. D. SANTIS, G. PERSIANO, AND U. VACCARO, *Randomness complexity of private computation*, Computational Complexity, 8 (1999), pp. 145–168, <https://doi.org/10.1007/s000370050025>, <https://doi.org/10.1007/s000370050025>.
- [6] P. BOGETOFT, D. L. CHRISTENSEN, I. DAMGÅRD, M. GEISLER, T. P. JAKOBSEN, M. KROIGAARD, J. D. NIELSEN, J. B. NIELSEN, K. NIELSEN, J. PAGTER, M. I. SCHWARTZBACH, AND T. TOFT, *Secure multiparty computation goes live*, in Financial Cryptography and Data Security, 13th International Conference, FC 2009, Accra Beach, Barbados, February 23–26, 2009. Revised Selected Papers, R. Dingledine and P. Golle, eds., vol. 5628 of Lecture Notes in Computer Science, Springer, 2009, pp. 325–343, https://doi.org/10.1007/978-3-642-03549-4_20, https://doi.org/10.1007/978-3-642-03549-4_20.
- [7] D. CHAUM, C. CRÉPEAU, AND I. DAMGÅRD, *Multiparty unconditionally secure protocols (extended abstract)*, in Proceedings of the 20th Annual ACM Symposium on Theory of Computing, May 2–4, 1988, Chicago, Illinois, USA, 1988, pp. 11–19, <https://doi.org/10.1145/62212.62214>, <https://doi.org/10.1145/62212.62214>.
- [8] B. CHOR AND E. KUSHILEVITZ, *A zero-one law for boolean privacy*, SIAM J. Discrete Math., 4 (1991), pp. 36–47, <https://doi.org/10.1137/0404004>, <https://doi.org/10.1137/0404004>.
- [9] B. CHOR AND E. KUSHILEVITZ, *A communication-privacy tradeoff for modular addition*, Inf. Process. Lett., 45 (1993), pp. 205–210, [https://doi.org/10.1016/0020-0190\(93\)90120-X](https://doi.org/10.1016/0020-0190(93)90120-X), [https://doi.org/10.1016/0020-0190\(93\)90120-X](https://doi.org/10.1016/0020-0190(93)90120-X).
- [10] I. DAMGÅRD, J. B. NIELSEN, R. OSTROVSKY, AND A. ROSÉN, *Unconditionally secure computation with reduced interaction*, in Advances in Cryptology - EUROCRYPT 2016 - 35th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Vienna, Austria, May 8–12, 2016, Proceedings, Part II, M. Fischlin and J. Coron, eds., vol. 9666 of Lecture Notes in Computer Science, Springer, 2016, pp. 420–447, https://doi.org/10.1007/978-3-662-49896-5_15, https://doi.org/10.1007/978-3-662-49896-5_15.
- [11] I. DAMGÅRD, J. B. NIELSEN, A. POLYCHRONIOU, AND M. A. RASKIN, *On the communication required for unconditionally secure multiplication*, in Advances in Cryptology - CRYPTO 2016 - 36th Annual International Cryptology Conference, Santa Barbara, CA, USA, August 14–18, 2016, Proceedings, Part II, M. Robshaw and J. Katz, eds., vol. 9815 of Lecture Notes in Computer Science, Springer, 2016, pp. 459–488, https://doi.org/10.1007/978-3-662-53008-5_16, https://doi.org/10.1007/978-3-662-53008-5_16.
- [12] D. DATA, V. M. PRABHAKARAN, AND M. M. PRABHAKARAN, *Communication and randomness lower bounds for secure computation*, IEEE Trans. Information Theory, 62 (2016), pp. 3901–3929, <https://doi.org/10.1109/TIT.2016.2568207>, <https://doi.org/10.1109/TIT.2016.2568207>.

- 2016.2568207.
- [13] A. GÁL AND A. ROSÉN, *A theorem on sensitivity and applications in private computation*, SIAM J. Comput., 31 (2002), pp. 1424–1437, <https://doi.org/10.1137/S0097539701385296>, <https://doi.org/10.1137/S0097539701385296>.
 - [14] A. GÁL AND A. ROSÉN, *Omega(log n) lower bounds on the amount of randomness in 2-private computation*, SIAM J. Comput., 34 (2005), pp. 946–959, <https://doi.org/10.1137/S0097539703432785>, <https://doi.org/10.1137/S0097539703432785>.
 - [15] O. GOLDREICH, *Modern Cryptography, Probabilistic Proofs and Pseudorandomness*, vol. 17 of Algorithms and Combinatorics, Springer, 1998, <http://link.springer.com/book/10.1007/978-3-662-12521-2/page/1>.
 - [16] A. JAKOBY, M. LIŚKIEWICZ, AND R. REISCHUK, *Private computations in networks: Topology versus randomness*, in STACS 2003, 20th Annual Symposium on Theoretical Aspects of Computer Science, Berlin, Germany, February 27 – March 1, 2003, Proceedings, H. Alt and M. Habib, eds., vol. 2607 of Lecture Notes in Computer Science, Springer, 2003, pp. 121–132, https://doi.org/10.1007/3-540-36494-3_12, https://doi.org/10.1007/3-540-36494-3_12.
 - [17] E. KUSHILEVITZ AND Y. MANSOUR, *Randomness in private computations*, SIAM J. Discrete Math., 10 (1997), pp. 647–661, <https://doi.org/10.1137/S0895480196306130>, <https://doi.org/10.1137/S0895480196306130>.
 - [18] E. KUSHILEVITZ, R. OSTROVSKY, E. PROUFF, A. ROSÉN, A. THILLARD, AND D. VERGNAUD, *Lower and upper bounds on the randomness complexity of private computations of AND*, in Theory of Cryptography - 17th International Conference, TCC 2019, Nuremberg, Germany, December 1-5, 2019, Proceedings, Part II, D. Hofheinz and A. Rosen, eds., vol. 11892 of Lecture Notes in Computer Science, Springer, 2019, pp. 386–406, https://doi.org/10.1007/978-3-030-36033-7_15, https://doi.org/10.1007/978-3-030-36033-7_15.
 - [19] E. KUSHILEVITZ, R. OSTROVSKY, AND A. ROSÉN, *Characterizing linear size circuits in terms of privacy*, J. Comput. Syst. Sci., 58 (1999), pp. 129–136, <https://doi.org/10.1006/jcss.1997.1544>, <https://doi.org/10.1006/jcss.1997.1544>.
 - [20] E. KUSHILEVITZ, R. OSTROVSKY, AND A. ROSÉN, *Amortizing randomness in private multiparty computations*, SIAM J. Discrete Math., 16 (2003), pp. 533–544, <http://epubs.siam.org/sam-bin/dbq/article/35274>.
 - [21] E. KUSHILEVITZ AND A. ROSÉN, *A randomness-rounds tradeoff in private computation*, SIAM J. Discrete Math., 11 (1998), pp. 61–80, <https://doi.org/10.1137/S089548019427634X>, <https://doi.org/10.1137/S089548019427634X>.
 - [22] N. NISAN AND A. TA-SHMA, *Extracting randomness: A survey and new constructions*, J. Comput. Syst. Sci., 58 (1999), pp. 148–173, <https://doi.org/10.1006/jcss.1997.1546>, <https://doi.org/10.1006/jcss.1997.1546>.
 - [23] A. ROSÉN AND F. URRUTIA, *A new approach to multi-party peer-to-peer communication complexity*, in 10th Innovations in Theoretical Computer Science Conference, ITCS 2019, January 10-12, 2019, San Diego, California, USA, A. Blum, ed., vol. 124 of LIPIcs, Schloss Dagstuhl - Leibniz-Zentrum fuer Informatik, 2019, pp. 64:1–64:19, <https://doi.org/10.4230/LIPIcs.ITCS.2019.64>, <https://doi.org/10.4230/LIPIcs.ITCS.2019.64>.